

Section 5

Section	Start Chainage	End Chainage	Length	Category	Note
Section 5	0	0	0	Handrails	Install single handrail either side of trail. 2 metres long, 1m tall, using 4-inch round posts. 1.2m between either rail.
Section 5	25	25	0	Drainage	Follow flag line carefully to form a series of meandering left and right hand turns. Maintain smooth radii, consistent gradient and good drainage throughout.
Section 5	35	35	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 5	55	55	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	67	67	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	80	80	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	90	95	5	Insloped Turn	Install pipe at insloped turn. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	100	100	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	105	105	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	120	120	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.

Section 5	135	135	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	135	140	5	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	150	185	35	Drainage	Install pipe at the right-hand turn. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	200	200	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	210	210	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	215	220	5	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	230	230	0	General	Insert
Section 5	230	235	5	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	245	245	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	250	255	5	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	275	275	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 5	280	360	80	Insloped Turn	Install pipe at the right-hand insloped turn. Ensure inlet and outlet are clear, protected and set with adequate fall.

Section 5	370	380	10	Berm	Install pipe at the right-hand berm. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	390	390	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	400	400	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	400	410	10	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	410	420	10	Berm	Install pipe at the right-hand berm. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	425	425	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	443	443	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	440	445	5	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 5	460	460	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 5	500	500	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	535	535	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	550	550	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.

Section 5	570	580	10	Stone Pitching	Install smooth stone pitching through this section. Set stones securely, provide a rideable surface, and ensure water is shed away from the trail.
Section 5	580	580	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 5	580	580	0	Handrails	Trail ends at the stated chainage. Tie trail neatly into the forest road and make good all disturbed edges. Install single handrail either side of trail exit. 2 metres long, 1m tall, using 4-inch round posts. 1.2m between either rail