

Section 8

Section	Start Chainage	End Chainage	Length	Category	Note
Section 8	0	0	0	Handrails	Install single handrail either side of trail. 2 metres long, 1m tall, using 4-inch round posts. 1.2m between either rail.
Section 8	5	15	10	Insloped turn	Form in-sloped left-hand insloped turn with smooth radius, compacted trail surface and adequate drainage.
Section 8	18	18	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 8	25	25	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 8	60	65	5	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 8	80	90	10	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	90	95	5	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	95	105	10	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	125	125	0	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	125	135	10	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.

Section 8	135	140	5	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	145	150	5	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	150	160	10	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	160	180	20	Drainage	Install pipe and build up the trail over the field boundary wall. Do not dig down; maintain positive drainage and compact imported material in layers.
Section 8	190	200	10	Berm	Form left-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	210	210	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	230	245	15	Berm	Form right-hand berm with smooth entry and exit radius, consistent crossfall and compacted trail surfacing.
Section 8	255	255	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	265	280	15	Drainage	Install pipe at the right-hand berm. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	280	300	20	Drainage	Install pipe at the left-hand berm. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	315	315	0	Roller	Insert roller with smooth entry and exit transitions and a compacted trail surface.
Section 8	325	325	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.

Section 8	340	340	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	355	355	0	Drainage	Install pipe. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	360	360	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	380	380	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	390	415	25	Switchback Turn	Form large level platform area for 180 degree turn right, topside drain required. Form a stable platform/ramp with smooth transitions, graded sides and no sudden or severe changes in gradient.
Section 8	420	420	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	425	425	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	435	435	0	Switchback Turn	Form large level platform area for 180 degree left hand berm, topside drain required. Form a stable platform/ramp with smooth transitions, graded sides and no sudden or severe changes in gradient.
Section 8	490	490	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	515	515	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.
Section 8	530	530	0	Drainage	Install pipe at the stated chainage. Ensure inlet and outlet are clear, protected and set with adequate fall.

Section 8	535	535	0	Handrails	Trail ends at the stated chainage. Tie trail neatly into the forest road and make good all disturbed edges. Install single handrail either side of trail exit. 2 metres long, 1m tall, using 4-inch round posts. 1.2m between either rail
-----------	-----	-----	---	-----------	---