

## Part L Specification

**BER IS NOT PUBLISHED**

### Property Details

Dwelling Type	Semi-detached house	Type of BER rating	New Dwelling - Provisional
Address line 1	shannon valley	Year of Construction	2008
Address line 2		Date of Assessment	04/11/2025
Address line 3		Date of Plans	
County	Co. Roscommon	Planning Reference	
Eircode		Building Regulations	2019 TGD L
BER Number		MPRN No.	10300740612
Purpose of Rating	Grant Support	Is MPRN shared with another dwelling?	Yes
Assessor Name	Darren Winston	Assessor Number	110142
Comment		BER number assigned to shared dwelling	N/A

### Dimension Details

	Area [m <sup>2</sup> ]	Height [m]	Volume [m <sup>3</sup> ]	
Ground Floor	60.58	2.30	139.33	
First Floor	60.54	2.68	162.25	
Second Floor	0.00	0.00	0.00	
Third and other floors	0.00	0.00	0.00	
Room in roof	0.00	0.00	0.00	
Total Floor Area	121.12		301.58	
Living Area [m <sup>2</sup> ]	25.60			Living area percentage [%] 21.14
No of Storeys	2			

### Ventilation Details

	Number		
Chimneys	0	Has permeability test been carried out?	Yes
Open Flues	0	Structure type	N/A
Fans & Vents	3	Is there a suspended wooden ground floor?	No
Number of flueless combustion room heaters	0	Percentage windows/doors draught stripped [%]	N/A
Is there a draught lobby on main entrance?	No	Number of sides sheltered	2
Ventilation method	Whole-house extract ventilation	Mechanical Ventilation Manufacturer	N/A
Specific fan power [W/(L/s)]	0.240	Mechanical Ventilation Model Name	N/A
Heat exchanger efficiency [%]	N/A	How many wetrooms (incl. kitchen)?	N/A

### Building Elements - Floor Details

Type	Description	Underfloor heating	U-Value [W/m <sup>2</sup> K]	Area [m <sup>2</sup> ]
Ground Floor - Solid	GF	No	0.37	60.58
Non-Heat Loss Floor	FF	N/A	0	60.54

### Building Elements - Roof Details

Type	Description	U-Value [W/m <sup>2</sup> K]	Area [m <sup>2</sup> ]
Pitched Roof - Insulated on Ceiling		0.27	60.54

### Building Elements - Wall Details

Type	Description	U-Value [W/m <sup>2</sup> K]	Area [m <sup>2</sup> ]
Unknown		0.37	86.18
300mm Cavity		0.21	11.04

### Building Elements - Door Details

Description	Number of Doors	U-Value [W/m <sup>2</sup> K]	Area [m <sup>2</sup> ]
D1 front	1	3	3.100
D2 rear	1	3	2.100

DRAFT

## Building Elements - Window Details

Glazing type	User defined u-value	U-Value [W/m <sup>2</sup> K]	Area [m <sup>2</sup> ]
Double-glazed, air filled (low-E, en = 0.15, hard coat)	Yes	2.000	4.350
Double-glazed, air filled (low-E, en = 0.15, hard coat)	Yes	2.000	5.490
Double-glazed, air filled (low-E, en = 0.15, hard coat)	Yes	2.000	1.490

DRAFT

## Other Details

Thermal bridging factor [W/m <sup>2</sup> k]	0.0800	Thermal mass category of dwelling	Medium-low
--	--------	-----------------------------------	------------

### Heating System - Solar Water Heating

Solar Water Heating Present?	No	Aperture area of solar collector [m <sup>2</sup> ]	N/A
Type, manufacturer, model	N/A	Collector heat loss coefficient, a1 [W/m <sup>2</sup> >K]	N/A
Zero loss collector efficiency, n0	N/A	Overshading factor	N/A
Annual Solar Radiation [kWh/m <sup>2</sup> ] (Refer to Appendix H in DEAP)	N/A	Combined Cylinder	N/A
Dedicated storage volume [Litres]	N/A		
Solar fraction [%]	0.000		

### Heating System - Hot Water System

Distribution Losses	308.94	Combi boiler present?	No
Supplementary electric water heating	N/A	Water Storage Volume [L]	200
Hot water storage manufacturer and model name	Midea 200LTR	Declared loss factor [kWh/d]	1.30
Temperature factor unadjusted	0.6	Temperature Factor Multiplier	0.9
Primary Circuit loss type	Boiler / heat pump with insulated primary pipework and with cylinder thermostat		
Is hot water storage indoors or in group heating system?	Yes	Insulation type	N/A
Insulation thickness [mm]	N/A		

### Heating System - Dist. system losses and gains

Temperature adjustment [°C]	0	Control Category	3	Responsiveness category	1
Central heating pumps	1	Oil Boiler Pump	0	Oil boiler pump inside dwelling	No
Gas boiler flue fan	0	Warm air heating or fan coil radiators present	No		

### Heating System - Energy Requirements (Individual)

Main space heating system efficiency [%]	547.43	Space heating efficiency adjustment factor	1.0000	Main space heating fuel	Electricity
Main water heating system efficiency [%]	210.05	Water heating efficiency adjustment factor	1.0000	Main water heating fuel	Electricity
Secondary heating system efficiency [%]	N/A	Fraction of heating from secondary heating system	N/A	Secondary space heating system fuel	None
Fraction of main space and water heat from CHP	N/A	Electrical efficiency of CHP	N/A	Heat efficiency of CHP	N/A
CHP Fuel type	N/A				

### Summary for Part L Conformance (Applies to TGD L 2008/2011/2019 for new dwellings only)

BER Number		Building Regulations	2019 TGD L
BER Result	A2	Energy Value kWh/m <sup>2</sup> /yr	40.50
CO <sub>2</sub> emissions [kg/m <sup>2</sup> /yr]	5.18		
EPC	0.287	EPC Pass/Fail	Pass
CPC	0.185	CPC Pass/Fail	Pass

### Part L Conformance - Fabric

Conformity with Maximum avg U-value requirements	U-value [W/m <sup>2</sup> K]	Pass/Fail	Conformity with Maximum U-value requirements	U-Value [W/m <sup>2</sup> K]	Pass/Fail
Pitched roof insulated on ceiling	0.27	Fail	Roofs	0.27	Pass
Pitched roof insulated on slope	0	Pass	Walls	0.37	Pass
Flat Roof	0	Pass	Floors	0.37	Pass
Floors with no underfloor heat	0.37	Fail	External doors / windows / rooflights	3.00	Pass
Floors with underfloor heat	0.00	Pass	Meets Part L maximum avg U-value requirement for opaque elements using TGD L Section 1.3.2.3		Fail
Walls	0.35	Fail			
Percentage of opening areas [%]	13.65				
Average U value of openings	2.31	Fail			
Permeability test carried out and meets guidelines in TGD L				0.15	Pass

Part L Conformance - Renewables (applies to TGD L 2019)

	Source	Renewables Primary Energy	Total Primary Energy	RER
+ Delivered energy	PV/Wind	0.00	0.00	
+ Delivered energy	Other	0.00	0.00	
+ Delivered energy	Solar	0.00	0.00	
+ Delivered energy	Biomass	0.00	0.00	
+ Delivered energy	Biodiesel	0.00	0.00	
+ Delivered energy	Bioethanol	0.00	0.00	
+ Environmental energy	HP	6037.03	6037.03	
+ Saved energy	CHP	0.00	0.00	
+ District heating	District Heating	0.00	0.00	
+ Delivered energy	Grid	0.00	4905.00	
+ Delivered energy	Thermal	0.00	0.00	
<b>SUBTOTAL</b>		<b>6037.03</b>	<b>10942.03</b>	<b>0.55 - Pass</b>
Energy not used in Regulated Loads	PV/Wind/CHP	0.00	0.00	
<b>TOTAL</b>		<b>6037.03</b>	<b>10942.03</b>	<b>0.55</b>

DRAFT

## Energy Requirements: Individual Heating Systems

	Fuel Type	Electricity Fuel Factors Date	Primary energy conversion factor	CO <sub>2</sub> emission factor
<b>Main space heating system</b>	Electricity	Current	1.75	0.224
<b>Secondary space heating system</b>	None	Current	0.00	0.000
<b>Main water heating system</b>	Electricity	Current	1.75	0.224
<b>Cooling System</b>	None	Current	0.00	0.000
<b>Pumps, fans</b>	Electricity	Current	1.75	0.224
<b>Energy for lighting</b>	Electricity	Current	1.75	0.224

**DRAFT**