

S1

SERVICES LEGEND

UNDERGROUND ELECTRICITY LINE	FOUL DRAINAGE
ELECTRICAL MANHOLE	FOUL MANHOLE
OVERHEAD LINE WITH POLE	STORM DRAINAGE
OVERHEAD ELECTRIC	STORM DRAINAGE MANHOLE
UNDERGROUND HV ELECTRICITY LINE	COMBINED DRAINAGE
6M HIGH STREET LIGHT	COMBINED DRAINAGE MANHOLE
MINI PILLAR	PRODUCT DRAINAGE
UFG ELECTRIC TRAFFIC CONTROL	PRODUCT DRAINAGE MANHOLE
TRAFFIC CONTROL MANHOLE	CHEMICAL LINE
EIR	CHEMICAL MANHOLE
EIR CHAMBER	ROAD GULLY
OVERHEAD LINE WITH POLE	GULLY TRAP
ENET	WATER MAIN
ENET CHAMBER	SLUICE VALVE
COMMS	FIRE HYDRANT
COMMS CHAMBER	WATER METER
VIRGIN	SCOUR VALVE
VIRGIN CHAMBER	PRESSURE RELEASE VALVE
FIBRE	AIR VALVE
FIBRE CHAMBER	NON-RETURN VALVE
AURORA TELECOM	FUEL LINE/TANK
AURORA TELECOM CHAMBER	GAS SV
CATV	GAS LINE
CATV CHAMBER	GAS HIGH PRESSURE LINE
BT/ESAT	GL 00.00 GROUND LEVEL (METRES - OS DATUM)
BT/ESAT CHAMBER	CL 10.00 COVER LEVEL (METRES - OS DATUM)
SIRO FIBRE	IL 10.00 INVERT LEVEL (METRES - OS DATUM)
SIRO CHAMBER	DP1.50 DEPTH TO TOP OF SERVICE DUCT OR CABLE
UNIDENTIFIED SERVICE	DP ON MANHOLES = INVERT LEVEL OF CHAMBER
UNIDENTIFIED CHAMBER	DP ON DRAINAGE = INVERT LEVEL OF PIPE
EARTH LINE AND RODS	UTO UNABLE TO OPEN
TRAFFIC SENSORS	OSA OUTSIDE SURVEY AREA
CCTV POLE	UTT UNABLE TO TRACE
UTILITIES CABINET	SURVEYED AREA

SHEET LEGEND

Please note that the absence of services on this drawing is not solid proof that these services are not present in the ground.
While every method of underground utility locating has been adhered to in this survey, some services may lie outside the range of the GPR and electro-magnetic locator signal. Poor ground conditions and or services situated underneath other services can also prove impossible to locate. Due to the fact that not all Utility Service Plans were provided to Metroscan by the contractor,Metroscan cannot be held responsible for any services that have not been identified. The contractor should not assume that all services have been identified and must exercise a duty of care when excavating.
Hand / vacuum excavation is advised to determine exact depth and position of service prior to excavation commencing.
Please note that the drawing provided is valid for 60 days from date stated below.
Drawing is intended solely for use of the contractor named below.

Accuracy Levels

In ideal conditions the accuracy levels of the EML is +/-5% whilst the GPR outputs accuracy levels of 10% up to 2.5m depth.
These accuracy levels can vary depending on ground conditions, depths of services, congestion of services (may cause signal to bleed on to other services).
Depths noted on drawings should be taken as indicative and hand / vacuum excavation is advised where exact depth are required.
Diameter of services will be given where direct access is available through visual inspection, eg manhole.
All Cover level elevations for Manholes / Inspection Chambers will be taken from topographical survey if supplied

Survey Limitations
Non-conductible services pose a difficult task to identify. Direct buried fibre optic cables are difficult to identify with GPR.
They can easily be traced when placed in a conduit by the means of a sonde or cobra reel.
PE gas mains can also prove difficult to identify.

If Metroscan cannot get an accurate signal from a service, it will be noted on the drawing that the service is 'Taken from records QL-B4'.
If manholes cannot be opened on site, they will be marked on the drawing as UTO (unable to open).
Excluded from the survey unless otherwise stated :
Domestic services, Services above ground, Disconnected services where no signal can be obtained.

Notes

1. GPR equipment :
   Detector Duo, DS2000,
   Stream C, Mala EL Core
   scanning frequency 250 and 700 mhz
   Depth of investigation 2.5m, self calibrating.
2. Radio detection equipment:
   Vivax Metrotech VLoc Pro3 / RD7000
3. GPR scanning limited to smooth surfaces only no obstruction.
   Survey area marked on drawing
4. All depths stated are an indication of depth
   caution required when excavating.
5. All Utilities are classified QL- B2 unless noted otherwise.

PAS 128

Survey Type		Quality Level	Location Accuracy		Supporting Data
			Horizontal	vertical	
D	Desktop utility record search	QL-D	Undefined	Undefined	
C	Site Reconnaissance	QL-C	Undefined	Undefined	A segment of utility whose location is demonstrated by visual reference to street furniture, topographical features or evidence of previous street works.
B	Detection	QL-B4	Undefined	Undefined	A utility segment which is suspected to exist but has not been detected and is therefor shown as an assumed route
		QL-B3/ QL-B3P	plus/minus 500mm	Undefined (no reliable depth)	Horizontal location only of the utility detected by one of the geophysical technicques used
		QL-B2 / QL-B2P	plus/minus 250mm of the detected depth	Plus/minus 40% of the detected depth	Horizontal and vertical location of the utility detected by one of the geophysical technicques used
		QL-B1 / QL-B1P	plus/minus 150mm of the detected depth	plus/minus 15% of the detected depth	Horizontal and vertical location of the utility detected by multiple geophysical technicques used
A	Verification	QL-A	plus/minus 50mm	plus/minus 15mm	Horizontal and vertical location of the top and/or bottom of the utility through trial hand/slit trench method

Client : **Andrew Riley Consulting Engineers**

Site Address : Cherry Orchard Community Child Care Centre
Dublin 10

Drawing Title: MUL1298_Riley_Cherry Orchard		**Drwg No:**	1
Site Completion Date: 30th November 2022		**Sheet No:**	S1
Scale: 1:200 @ A1	**Coordinates:** ITM	**Revision No:**	

METROSCAN UTILITY LOCATING

Address: Rathjarney
Piercestown
Co. Wexford
Tel: (086)1935847

Email: Info@metroscan.ie

Website: www.metroscan.ie



SERVICES LEGEND

UNDERGROUND ELECTRICITY LINE		FOUL DRAINAGE	
ELECTRICAL MANHOLE	ENU	FOUL MANHOLE	FMH
OVERHEAD LINE WITH POLE		STORM DRAINAGE	
OVERHEAD ELECTRIC		STORM DRAINAGE MANHOLE	SMH
UNDERGROUND HV ELECTRICITY LINE	ESB HV	COMBINED DRAINAGE	
6M HIGH STREET LIGHT		COMBINED DRAINAGE MANHOLE	
MINI PILLAR	ESB MP/PL	PRODUCT DRAINAGE	
UFG ELECTRIC TRAFFIC CONTROL		PRODUCT DRAINAGE MANHOLE	
TRAFFIC CONTROL MANHOLE	TCM	CHEMICAL LINE	
EIR		CHEMICAL MANHOLE	CHEM
EIR CHAMBER	EIR	ROAD GULLY	
OVERHEAD LINE WITH POLE		GULLY TRAP	
ENET		WATER MAIN	
ENET CHAMBER	ENET	SLUICE VALVE	SV
COMMS		FIRE HYDRANT	FH
COMMS CHAMBER	COMMS	WATER METER	WM
VIRGIN		SCOUR VALVE	SCV
VIRGIN CHAMBER	VIRGIN	PRESSURE RELEASE VALVE	PRV
FIBRE		AIR VALVE	AV
FIBRE CHAMBER	FIBRE	NON-RETURN VALVE	NRV
AURORA TELECOM		FUEL LINE/TANK	
AURORA TELECOM CHAMBER	AURORA TELECOM	GAS SV	GSV
CATV		GAS LINE	
CATV CHAMBER	CATV	GAS HIGH PRESSURE LINE	GAS HP
BT/ESAT		GROUND LEVEL (METRES - OS DATUM)	GL 00.00
BT/ESAT CHAMBER	BT/ESAT	COVER LEVEL (METRES - OS DATUM)	CL 10.00
SIRO FIBRE		INVERT LEVEL (METRES - OS DATUM)	IL 10.00
SIRO CHAMBER	SIRO	DEPTH TO TOP OF SERVICE DUCT OR CABLE	DP1.50
UNIDENTIFIED SERVICE	UNID	DP ON MANHOLES = INVERT LEVEL OF CHAMBER	
UNIDENTIFIED CHAMBER	UNID	DP ON DRAINAGE = INVERT LEVEL OF PIPE	
EARTH LINE AND RODS		UNABLE TO OPEN	UTO
TRAFFIC SENSORS	SENSOR	OUTSIDE SURVEY AREA	OSA
CCTV POLE	CCTV	UNABLE TO TRACE	UTT
UTILITIES CABINET	GSC	SURVEYED AREA	

SHEET LEGEND

Please note that the absence of services on this drawing is not solid proof that these services are not present in the ground.
While every method of underground utility locating has been adhered to in this survey, some services may lie outside the range of the GPR and electro-magnetic locator signal. Poor ground conditions and or services situated underneath other services can also prove impossible to locate. Due to the fact that not all Utility Service Plans were provided to Metroscan by the contractor,Metroscan cannot be held responsible for any services that have not been identified. The contractor should not assume that all services have been identified and must exercise a duty of care when excavating.
Hand / vacuum excavation is advised to determine exact depth and position of service prior to excavation commencing.
Please note that the drawing provided is valid for 60 days from date stated below.
Drawing is intended solely for use of the contractor named below.

Accuracy Levels

In ideal conditions the accuracy levels of the EML is +/-5% whilst the GPR outputs accuracy levels of 10% up to 2.5m depth.
These accuracy levels can vary depending on ground conditions, depths of servcies, congestion of services (may cause signal to bleed on to other services).
Depths noted on drawings should be taken as indicative and hand / vacuum excavation is advised where exact depth are required.
Diameter of services will be given where direct access is available through visual inspection, eg manhole.
All Cover level elevations for Manholes / Inspection Chambers will be taken from topographical survey if supplied

Survey Limitations
Non-conductible services pose a difficult task to identify. Direct buried fibre optic cables are difficult to identify with GPR.
They can easily be traced when placed in a conduit by the means of a sonde or cobra reel.
PE gas mains can also prove difficult to identify.

If Metroscan cannot get an accurate signal from a service, it will be noted on the drawing that the service is 'Taken from records QL-B4'.
If manholes cannot be opened on site, they with be marked on the drawing as UTO (unable to open).
Excluded from the survey unless otherwise stated :
Domestic services, Services above ground, Disconnected services where no signal can be obtained.

Notes

1. GPR equipment :
   Detector Duo, DS2000,
   Stream C, Mala EL Core
   scanning frequency 250 and 700 mhz
   Depth of investigation 2.5m, self calibrating.
2. Radio detection equipment:
   Vivax Metrotech VLoc Pro3 / RD7000
3. GPR scanning limited to smooth surfaces only no obstruction.
   Survey area marked on drawing
4. All depths stated are an indication of depth
   caution required when excavating.
5. All Utilities are classified QL- B2 unless noted otherwise.

PAS 128

Survey Type		Quality Level	Location Accuracy		Supporting Data
			Horizontal	Vertical	
D	Desktop utility record search	QL-D	Undefined	Undefined	
C	Site Reconnaissance	QL-C	Undefined	Undefined	A segment of utility surface location is demonstrated by visual reference to street furniture, topographical features or evidence of previous street works.
B	Detection	QL-B4	Undefined	Undefined	A utility segment which is suspected to exist but has not been detected and is therefor shown as an assumed route
		QL-B3 QL-B3P	plus/minus 500mm	Unreliable (no reliable depth)	Horizontal location only of the utility detected by one of the geophysical techniques used
		QL-B2 QL-B2P	plus/minus 250mm of the detected depth	plus/minus 40% of the detected depth	Horizontal and vertical location of the utility detected by one of the geophysical techniques used
		QL-B1 QL-B1P	plus/minus 150mm of the detected depth	plus/minus 15% of the detected depth	Horizontal and vertical location of the utility detected by multiple geophysical techniques used
A	Verification	QL-A	plus/minus 50mm	plus/minus 10mm	Horizontal and vertical location of the top and/or bottom of the utility through trial hand/slit trench method

Client : **Andrew Riley Consulting Engineers**

Site Address : Cherry Orchard Community Child Care Centre
Dublin 10

Drawing Title: MUL1298_Riley_Cherry Orchard		**Drwg No:**	1
Site Completion Date: 30th November 2022		**Sheet No:**	S2
Scale: 1:200 @ A1	**Coordinates:** ITM	**Revision No:**	

METROSCAN UTILITY LOCATING

Address: Rathjarney
Piercestown
Co. Wexford
Tel: (086)1935847

Email: Info@metroscan.ie

Website: www.metroscan.ie