

DOORS SCHEDULE - Internal: Toilets							
DOOR TYPE 16		DOOR TYPE 17		DOOR TYPE 18		DOOR TYPE 19	
pull handles to comply with part M Horizontal pull handle 900mm above FFL. min. CO. 800 Pull handle to comply with part M		pull handles to comply with part M Horizontal pull handle 900mm above FFL. min. CO. 750		pull handles to comply with part M Horizontal pull handle 900mm above FFL. Pull handle to comply with part M min. CO. 800		pull handles to comply with part M Horizontal pull handle 900mm above FFL. Pull handle to comply with part M min. CO. 1000	
NOTE: ACC. TOILETS, ACC. SHOWER/CHANGING ROOM		NOTE: STAFF WC CUBICLE		NOTE: ACC. TOILETS		NOTE: SEN ASSISTED USER'S TOILET/SHOWER	
Tag: D04, D05, D15, D20, D23, D27, D42 Min. clear door opening 800mm (MAINSTREAM CLASSROOM ENSUITE TOILETS min CO. 750mm or AWAP) Softwood painted selected colour Qty. 7 Hinges 3 No. stainless steel Self Closer Ball bearing hinges Focus contract door closer Handle 2 No. Focus premier pull handles Push Plate 2 No. Finger plates Latch Accessible thumb-turn lock with indicator, emergency operable from outside Door Stop selected Accessories 2 No. Kicking plate Coat Hook Signage Accessible WC; Ambulant Toilet		Tag: D10 Min. clear door opening 750mm or AWAP Softwood painted selected colour Qty. 1 Hinges 3 No. stainless steel Closer Ball bearing hinges Focus contract door closer Handle 2 No. lever handle, rose and escutcheon Latch Thumb-turn lock with indicator, emergency operable from outside Door Stop Selected Accessories 2 No. Kicking plate Signage safety glass vision panel Unisex Toilet		Tag: D11, D14, D19, D22, D41 Min. clear door opening 800mm (MAINSTREAM CLASSROOM ENSUITE TOILETS min CO. 750mm or AWAP) Softwood painted selected colour Qty. 5 Hinges 3 No. stainless steel Self Closer Ball bearing hinges Focus contract door closer Handle 2 No. Focus premier pull handles Push Plate 2 No. Finger plates Latch Accessible thumb-turn lock with indicator, emergency operable from outside Door Stop selected Accessories 2 No. Kicking plate Coat Hook Signage Accessible WC		Tag: D43 Min. clear door opening 800mm Softwood painted selected colour Qty. 1 Hinges 3 No. stainless steel Self Closer Ball bearing hinges Focus contract door closer Handle 2 No. Focus premier pull handles Push Plate 2 No. Finger plates Latch Accessible thumb-turn lock with indicator, emergency operable from outside Door Stop selected Accessories 2 No. Kicking plate Coat Hook Signage Accessible WC	

DOORS SCHEDULE - Internal: Double Doors			
DOOR TYPE 22	DOOR TYPE 23	DOOR TYPE 24	DOOR TYPE 25
NOTE: MAINSTREAM AREA MAIN ENTRANCE LOBBY	NOTE: Block C CORRIDOR - TO EXISTING CLASSROOM	NOTE: SEN LOBBY	NOTE: SEN LOBBY, CENTRAL ACTIVITIES
Tag: D01 Min. clear door opening 1000mm Softwood painted selected colour Qty. 1 Hinges 4 No. stainless steel Ball bearing hinges Closer Automatic closer Handle 2 No. lever handle, rose and escutcheon Door Stop Selected Other 2 No. Kicking plate safety glass vision panel	Tag: D28 Min. clear door opening 1000mm Softwood painted selected colour Qty. 1 Hinges 4 No. stainless steel Ball bearing hinges Closer Automatic closer Handle 2 No. lever handle, rose and escutcheon Door Stop Selected Other 2 No. Kicking plate safety glass vision panel	Tag: D32 Min. clear door opening 1000mm Softwood painted selected colour Qty. 1 Hinges 4 No. stainless steel Ball bearing hinges Closer Automatic closer Handle 2 No. lever handle, rose and escutcheon Door Stop Selected Other 2 No. Kicking plate safety glass vision panel	Tag: D09, D31 FD30S Min. clear door opening 800mm Softwood painted selected colour Qty. 2 Hinges 4 No. stainless steel Ball bearing hinges Self Closer Focus contract door closer Handle 4 No. lever handle, rose and escutcheon selected Door Stop 4 No. Kicking plate Accessories 2 No. safety glass vision panels; glazed overpanel Signage "Fire door keep shut"

DOORS SCHEDULE - Internal: Double Swing	
DOOR TYPE 20	DOOR TYPE 21
NOTE: CROSS CORRIDOR DOORS - to be held on electromagnetic hold open devices interfaced with the fire alarm. EM catches shall fail safe to release the doors on main power failure and shall be provided with a manual override facility.	NOTE: CROSS CORRIDOR DOORS - Block C: Refer to F5C Condition 5
Tag: D12, D17, D24 FD.30S Min. clear door opening 800mm Softwood painted selected colour Qty. 3 Hinges 6 No. stainless steel Ball bearing hinges Self Closer Focus contract door closer double action Handle 4 No.lever handle, rose and escutcheon Door Stop selected Accessories 4 No. Kicking plate 2 No. safety glass vision panels Signage "Fire door keep shut"	Tag: D25 FD.60S Min. clear door opening 800mm Softwood painted selected colour Qty. 1 Hinges 6 No. stainless steel Ball bearing hinges Self Closer Focus contract door closer double action Handle 4 No.lever handle, rose and escutcheon Door Stop selected Accessories 4 No. Kicking plate 2 No. safety glass vision panels Signage "Fire door keep shut"

DOORS SCHEDULE - Internal: Storage Double Doors																													
DOOR TYPE 26	DOOR TYPE 27																												
Tag: D07, D08 FD.30S Softwood painted selected colour <table> <tr> <td>Qty.</td> <td>2</td> </tr> <tr> <td>Hinges</td> <td>6 No. stainless steel Ball bearing hinges</td> </tr> <tr> <td>Closer</td> <td>-</td> </tr> <tr> <td>Handle</td> <td>2 No. lever handle</td> </tr> <tr> <td>Lock</td> <td>Mortice sash lock</td> </tr> <tr> <td>Door Stop</td> <td>Selected</td> </tr> <tr> <td>Signage</td> <td>"Fire door keep shut"</td> </tr> </table>	Qty.	2	Hinges	6 No. stainless steel Ball bearing hinges	Closer	-	Handle	2 No. lever handle	Lock	Mortice sash lock	Door Stop	Selected	Signage	"Fire door keep shut"	Tag: D29, D39 FD.30S Softwood painted selected colour <table> <tr> <td>Qty.</td> <td>2</td> </tr> <tr> <td>Hinges</td> <td>4 No. stainless steel Ball bearing hinges</td> </tr> <tr> <td>Closer</td> <td>-</td> </tr> <tr> <td>Handle</td> <td>2 No. lever handle</td> </tr> <tr> <td>Lock</td> <td>Mortice sash lock</td> </tr> <tr> <td>Door Stop</td> <td>Selected</td> </tr> <tr> <td>Signage</td> <td>"Fire door keep shut"</td> </tr> </table>	Qty.	2	Hinges	4 No. stainless steel Ball bearing hinges	Closer	-	Handle	2 No. lever handle	Lock	Mortice sash lock	Door Stop	Selected	Signage	"Fire door keep shut"
Qty.	2																												
Hinges	6 No. stainless steel Ball bearing hinges																												
Closer	-																												
Handle	2 No. lever handle																												
Lock	Mortice sash lock																												
Door Stop	Selected																												
Signage	"Fire door keep shut"																												
Qty.	2																												
Hinges	4 No. stainless steel Ball bearing hinges																												
Closer	-																												
Handle	2 No. lever handle																												
Lock	Mortice sash lock																												
Door Stop	Selected																												
Signage	"Fire door keep shut"																												

DOOR/DOORS CLEAR OPENING (CO.):

Minimum effective clear width of doors to wheelchair accessible areas taken to be a min. 800mm clear width unless otherwise stated.

The width of a doorway shall be the effective clear width through a single door or at least one leaf of a double door when the door or doors are open. Measurement shall be taken from the point on the door or door hardware which protrudes most into the width to the nearest point of the door frame or door stop. Door hardware protruding into this width must be considered to reduce the effective clear width. Swing door or doors shall be free to open to an angle of at least 90°.

Note: The CO. shown on the Doors Schedule is the minimum required CO. in accordance with the FSC/DAC drawings and specifications.

Read in conjunction with FSC/DAC drawings and specifications for minimum Clear Openings, Division panels requirements, Clear Space to leading edge of doors etc.

DOOR SIGNS/MARKS:

Install all door signage at eye level (56" minimum) above FFL to the center of the sign (e.g. 'Fire Door - Keep Shut')

Refer to room floor plans for correct room names and sign text (e.g. 'Staff Toilet', 'Unisex Toilet', etc.)

Ensure signage is level, securely fixed, and clearly visible when door is in the closed position.

FINGER GUARDS

All doors serving SEN accommodation shall be provided with proprietary protective finger guards to the hinged edge of the door, in accordance with the Department of Education guidelines.

Finger guard systems shall be suitable for the door type and intended use, coordinated with hinges, frames, closers and ironmongery, and shall not compromise the fire, smoke or acoustic performance of any rated doorset.

Provide protection to all accessible finger-entrapment points at the hinge side of the door.

NOTES :

This drawing is copyright and may not be copied or altered without permission.

Use only figured dimensions. Do not scale this drawing.

The contractor is responsible for checking all dimensions on site prior to construction.

The Architects are to be notified of any discrepancies prior to work

commencing.

Levels and contours, shown on drawings, are relative to local datum unless specified

[illegible]

PROJECT: QUEEN OF ANGELS PRIMARY SCHOOL			
ADDRESS: Additional Accommodation			
DRAWING: Wedgewood, Sandyford, Dublin, 16			
DOORS SCHEDULE (2 of 2)			
SCALE: 1:50		DWG. NO.: 22518-TEN-004	
22518-TEN	DATE: 24.09.2025	REV:	
MC			

