

FINISHES SCHEDULE
INVER COLLEGE, CARRICKMACROSS, CO. MONAGHAN 26-015

ROOM	WALLS	CEILING	FLOOR	OTHER	
Science Classroom	Existing wall surface to be made good following removal of built in furniture. 2 coats silk vinyl emulsion- low sheen on all walls. Spec ref M60 painting.	Existing exposed underside of roof to be retained. Any services to be removed/rerouted to be carefully dismantled and made good where any damage is done during strip-out and re-fit. Underside of roof panel to be thoroughly cleaned. Exposed structural steel to be painted with 2 coats silk vinyl emulsion - low sheen Spec ref M60 painting.	Existing vinyl sheet flooring along with adhesive and residues to be removed throughout. Proprietary waterbased levelling compound to be smoothed over existing floor to a thickness of 3-5mm to ensure no undulations/indentations are present. heterogeneous Vinyl floor covering with Slip resistance of R10, SRV 36 + 20 microns, compliant with EN14041- Electrostatic rating and with a Commercial 34 EN ISO 10874: Flooring Use Classification for durability Spec Ref:M50 150 Type A skirting 770	Fitted furniture as per dwgs RE-01, A-01 & A-02 And spec N10, N11 & N13 1 x whiteboard 1.2 x 1.2m & 2 x pinboard 1.2.x 1.2m. Also see equipment schedule, laboratory fittings, fixed furniture & loose furniture schedules on dwg P-01.	
Prep Room	Existing wall surface to be made good following removal of built in furniture. 2 coats silk vinyl emulsion- low sheen on all walls. Spec ref M60 painting.	Existing suspended ceiling to be removed. 30 minute fire rated ceiling to be installed as per detail on dwg A-02 Skim plaster finish with 3 coats silk vinyl emulsion - low sheen Spec Ref: M60 painting K10 Fire rated ceiling	Existing vinyl sheet flooring along with adhesive and residues to be removed throughout. Proprietary waterbased levelling compound to be smoothed over existing floor to a thickness of 3-5mm to ensure no undulations/indentations are present. heterogeneous Vinyl floor covering with Slip resistance of R10, SRV 36 + 20 microns, compliant with EN14041- Electrostatic rating and with a Commercial 34 EN ISO 10874: Flooring Use Classification for durability Spec Ref:M50 150 Type A skirting 770	Fitted furniture as per dwgs RE-01, A-01 & A-02 And spec N10, N11 & N13 Also see equipment schedule, laboratory fittings, fixed furniture & loose furniture schedules on dwg P-01.	
Chemical store	Existing wall surface to be repainted. 2 coats silk vinyl emulsion- low sheen on all walls. Spec ref M60 painting.	Existing suspended ceiling to be removed. 30 minute fire rated ceiling to be installed under existing ceiling as per detail on dwg A-02 Skim plaster finish with 3 coats silk vinyl emulsion - low sheen Spec Ref: M60 painting K10 Fire rated ceiling	Existing vinyl sheet flooring along with adhesive and residues to be removed throughout. Proprietary waterbased levelling compound to be smoothed over existing floor to a thickness of 3-5mm to ensure no undulations/indentations are present. heterogeneous Vinyl floor covering with Slip resistance of R10, SRV 36 + 20 microns, compliant with EN14041- Electrostatic rating and with a Commercial 34 EN ISO 10874: Flooring Use Classification for durability Spec Ref:M50 150 Type A skirting 770	NIL	